

Eaton 3S



Technology: Series 3 (Standby)
 Rating: 550 & 700VA
 Voltage: 240Vac
 Backup time: Typical 5 min
 Configuration: Powerboard style



Protection against power problems

- The Eaton 3S UPS helps to protect your computer equipment in case of everyday events (lightning strikes, storms, over-demand on the utility grid, accidents, and natural disasters) knocking out power without warning
- In the event of a total blackout, the unit provides sufficient battery backup time to last through most power outages
- The 700VA model saves up to 30% energy through its EcoControl function which automatically disables peripherals when the master device (ie. a computer) is turned off
- The 3S also protects telephone, broadband and Ethernet line from "back door" power surges
- The shutdown software makes it possible to automatically save your work and shut down your application without losing any data. Once the power is restored, you can continue working exactly where you left off

Easy integration and installation

- Attractive design and glossy finish make the 3S a perfect fit for the modern office environment
- The 3S comes with a fixed input cable and 6 Australian outlets for easy connection of typical computer configurations with peripherals
- The 3S features a HID-compliant USB port (cable supplied), for automatic integration with common operating systems (Windows/Mac OS/Linux)
- Compact unit fits on or under your desk or can be mounted on a wall
- Easy-to-replace battery helps to extend UPS service life

Ideal for protecting

- Computers and peripherals
- Broadband modems (internet and TV)
- IP telephony equipment
- POS equipment

Eaton 3S Technical specifications

Rating (VA/W)	550VA / 330W	700VA / 420W
Model numbers	3S550AU	3S700AU
Output connection	3 x Aust 3 Pin 10A outlets with battery backup and surge protection + 3 x Aust. 3 Pin 10A outlets with surge protection	
Characteristics		
Input voltage	Up to 161-284 V (adjustable)	
Output voltage	240 V (settable to 220 V, 230 V or 240 V)	
Frequency	50-60 Hz autoselect	
Input protection	Resettable circuit breaker	
Features		
ECO Control	No	Yes
Line protection	Tel/fax/modem/internet/Ethernet	
Battery		
Battery type	Compact, sealed lead-acid (replaceable)	
Battery test	Yes	Yes
Cold start (no mains power)	Yes	Yes
Deep-discharge protection	Yes	Yes
Battery replacement indicator	LED	LED
Runtime at 50% load	10 min	9 min
Runtime at 70% load	6 min	6 min
Communication	Communications port HID-compliant USB port for automatic integration with most common operating systems. USB cable supplied	
Standards compliance		
Safety/EMC	IEC 62040-1, IEC 60950-1, IEC 62040-2, CB Report, CE mark, C-Tick, A-Tick	
EMC	IEC 62040-2, C-Tick	
Dimensions and weight		
Dimensions H x W x D	86 x 140 x 335 mm	86 x 170 x 335 mm
Weight	2.9 kg	3.8 kg
Warranty	2 year	
Warranty+	Optional Warranty Uplifts	

Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.